



BIOtrenn E 20 / E 40

Mineral Oil-free Separating Agent for
Hard Wood Pallets – Biodegradable -

Product Information:

Properties:

BIOtrenn E 20 / E 40 penetrates the wood surface and impregnates the boards allowing a slight and non-damaging separation between wood and concrete. **BIOtrenn E 20 / E 40** prevents tearing of wood fibres and gap formation as well as the dehydration of concrete slabs. **BIOtrenn E 20 / E 40** is free of organic solvents.

Application:

BIOtrenn E 20 / E 40 is used for preventing concrete paving blocks, slabs etc. from sticking to pallets on block making machines.

Notes on processing:

Primarily daily treatment is important, particularly when using new pallets. It is reasonable to apply **BIOtrenn E 20 / E 40** automatically with an appropriate spray system. **BIOtrenn E 20 / E 40** is a stable oil-water emulsion and can be diluted with water in a ratio of 1 : 5 or 1 : 10 respectively. A new wooden shuttering should be treated at least for 10 min. prior to concreting.

Quantities to Use:

20 – 50 g/m² depending on the type and absorbency of the supporting boards and the degree of dilution

Specifications:

Colour:	white	
Density:	0.98 ± 0.01 g/ml	
Storage:	Protect against frost and contamination. Under normal storage conditions (closed container, 20 °C) minimum shelf-life 12 months.	
Supplied in:	container	approx. 1,000 l
	drum	210 l
	can	20 l

Safety Rules:

See EC Safety Data Sheet.

Assistance:

Please contact our Technical Application Centre.