



ECOtrenn (N)

Separating Agent for Non-Absorbing Shutterings

Product Information:

Properties:

ECOtrenn (N) has been developed on the basis of the latest technical and ecological knowledge. Corrosion inhibiting and preservative components prevent the shuttering from getting rusty. **ECOtrenn (N)** is quickly biodegradable.

Application:

ECOtrenn (N) can be used for all common shutterings. In case of heating the shuttering, the temperature should not exceed 60 °C.

Notes on processing:

ECOtrenn (N) is applied with a spray system (wide jet) to the shuttering in a very thin layer. The shuttering should be dry and clean to obtain the full effect of the thin layer. The product is delivered ready for application and may not be diluted.

Quantities to Use:

10 – 25 g/m² depending on the absorbency of the shuttering

Additional information:

ECOtrenn (N) is biodegradable for approx. 94 %, as per CEC test L-33-T-82.

Specifications:

Colour:	light amber	
Density:	0.82 ± 0.01 g/ml	
Storage:	Protect against frost and contamination. Under normal storage conditions (closed container, 20 °C) minimum shelf-life 12 months.	
Supplied in:	container	approx. 1,000 l
	drum	210 l
	can	20 l

Safety Rules:

See EC Safety Data Sheet.

Assistance:

Please contact our Technical Application Centre.