



REBAtrenn Universal

Separating Agent on Mineral Oil Basis

Product Information:

Properties:

REBAtrenn Universal effects an even, cost-saving coating and clean and fast releasing. The concrete surface is not affected. **REBAtrenn Universal** reduces the forming of rust spots, is insoluble in water, has a weak odour and does not become gummy. The oil film provides a good separating effect of the concrete from the shuttering.

Application:

For all types of shutterings in the structural and civil engineering, in the production of prefabricated elements and in the concrete industry.

Notes on processing:

REBAtrenn Universal is to be applied by spraying or brushing to a clean, dry surface and, if necessary, to be drawn off with an oil-proof foam slide. The treated surfaces or shapes can immediately be used or in certain intervals. They should, however, be protected from heavy rain. Concrete surfaces that are to be plastered should not have any form-oil residues, and best results are obtained by using absorbing wooden shutterings.

Quantities to Use:

15 – 50 g/m² depending on the type and absorbency of the shuttering

Specification:

Colour: amber

Density: 0.89 ± 0.01 g/ml

Storage: Protect from frost and contamination. Under normal storage conditions (closed container, 20 °C) minimum shelf-life approx. 12 months.

Supplied in: container approx. 1,000 l
 drum 210 l
 can 20 l

Safety Rules:

See EC Safety Data Sheet.

Assistance:

Please contact our Technical Application Centre.