

REBA_{tex} BI

Impregnation for application in the circulation process
Product No.: 250250

Product Information:

Properties:

- quick-drying
- solvent-free
- dirt-repelling effect

Application:

mineral surfaces
for all types of refined surfaces

All tools have to be cleaned with water immediately upon use. Avoid exposure to the sun during application. After approx. 30 sec. the impregnated concrete parts are non-adhesive and can be stacked and/or palletized. The total drying time is approx. 20 min. The surface has to be consistent, clean and absorbent. Matt-humid surfaces are suitable as well. REBA_{tex} BI is smoothly applied to the surface to be treated with a brush. In case of several applications REBA_{tex} BI has to be applied wet-on-wet. For permanent impregnation during the concrete production process we recommend application by spraying (e. g. BPB-EASY-SPRAY system).

Quantities to use:

100 - 300 g/m²

The specified quantities are approximate values because the actual applied quantity does not only depend on the surface structure, but also on the absorbency of the surface.

Preliminary tests on varnished and non-absorbing surfaces have to be conducted before application.

Specifications:

Appearance:	liquid
Colour:	colourless, opaque
Density:	1.05 ± 0.02 g/ml

Storage:

Protect against frost and dirt. Under normal storage conditions (closed container, 20 °C) minimum shelf-life 6 months.

Packaging:

container approx. 1000 kg, drum approx. 210 kg, can approx. 20 kg
exact quantity delivered on request

Safety Rules:

See EC safety data sheet.

Assistance:

Please contact our Technical Application Centre.